

**Claims**

- 1        1.        A pole apparatus comprising:  
2                a telescoping tubular body, said body defining an aperture extending  
3                into the interior of the body and having an open end and a closed end;  
4                a first connector mounted on the open end of said body, said connector  
5                defining a axial bore in communication with said interior of the body; and  
6                a second connector mounted on said closed end of said body, said  
7                second connector having a base and a arm extending outwardly from said base  
8                and in axial alignment with said body; and  
9                a tool, said tool having a mounting portion adapted to engage and be  
10                removably secured within said bore of said first connector and a head portion.  
  
1               2.        The pole apparatus of claim 1, wherein said first connector  
2                further comprises at least one alignment face.  
  
1               3.        The pole apparatus of claim 1, wherein said first connector  
2                further comprises a locking screw;  
  
1               4.        The pole apparatus of claim 1, wherein said head portion further  
2                comprises a threaded stud.  
  
1               5.        The pole apparatus of claim 1, wherein said head portion further  
2                comprises cylindrical body extending upwardly from a base, said body having

3 a tapered top portion and defining a bore 88 in axial alignment with the  
4 telescoping tubular body of the pole apparatus.

5

1 6. The pole apparatus of claim 5, wherein said bore of said head  
2 portion further comprises a hexagonal bore.

1 7. The pole apparatus of claim 1, wherein first connector further  
2 comprises a hexagonal side wall.

1 8. The pole apparatus of claim 7, wherein said upper portion and  
2 lower portion further comprises a body, said body having a central channel in  
3 axial alignment with the telescoping tubular body of the pole apparatus, at least  
4 one, two secondary channels 110 extending perpendicularly from central  
5 channel, and a front surface having a first and a second wall extending away  
6 from each side, respectively, said central channel at an acute angle relative to  
7 the channel.

1 9. An improved pole tool apparatus of the type in which a telescoping  
2 tubular body has an aperture extending into the interior of the body and at least  
3 one open end, wherein the improvement comprises:

4 a connector mounted on said open end of the body, said connector  
5 defining an axial bore in communication with said interior of the body,

6           a tool, said tool having a mounting portion adapted to engaged and be  
7       removably secured within the bore of said connector and a head portion, said  
8       head portion defining a hexagonal bore.

1       10.    A pole apparatus comprising:  
2           an elongated body, said body having an adjustable length and at least  
3       one end;  
4           a female connector affixed on said end of said body;  
5           a tool, said tool having a head portion and a male mounting portion  
6       adapted to engage be removably secured within the connector.